

<b>Weyfringe Applicator Technical Specification Comparison</b>				
<b>MODEL</b>	<b>SERIES 6000</b>	<b>SERIES 7000</b>	<b>RTL</b>	<b>DB4</b>
<b>MAX. LABEL APPLY SPEED*</b>	100 labels/min	100 labels/min	55 labels/min	45 labels/min
<b>MAX. LABEL WIDTH</b>	114mm	170mm	118-170mm**	116mm
<b>MAX. LABEL LENGTH</b>	150mm	250mm	330mm	205mm
<b>MAX. LABEL ROLL DIAMETER</b>	203mm	254mm	350mm	205mm
<b>MAX. RIBBON LENGTH</b>	N/A apply only	N/A apply only	450m	450m
<b>PRINT RESOLUTION</b>	N/A apply only	N/A apply only	203 - 300dpi	203 - 300dpi
<b>PRINT TYPE</b>	N/A apply only	N/A apply only	Direct/Thermal Transfer	Direct/Thermal Transfer
<b>APPLY ORIENTATION</b>	Wipe on (optional ram, tamp, tamp blow)	Wipe on (optional ram, tamp, tamp blow)	Top, side, front, tamp, tamp blow	Top, bottom, side, wraparound
<b>APPLY TOLERANCE</b>	+/- 2.5mm	+/- 2.5mm	+/- 0.6mm	+/- 3mm
<b>CONVEYOR SPEED</b>	40m/min	40m/min	Throughput dependent	12m/min
<b>INTERFACES</b>	N/A stand alone	N/A stand alone	Parallel, USB, RS232, ethernet,(optional wireless)	RS232, USB, ethernet (optional wireless)

\*Product and label size dependant

\*\*Applies to wide label models