

Rewind Unit

The Multi-Compatible Label Rewind Unit

The Rewind Unit has an intelligent idler arm allowing labels to be inside or outside wound onto a choice of core sizes at output sensitive speeds of up to 305mm per second.



**DEMONSTRATIONS
ON REQUEST**

WEYFRINGE LABELLING SYSTEMS

Longbeck Road | Marske-by-the-Sea | North Yorkshire | TS11 6HQ
Tel: 01642 490121 Fax: 01642 490385
sales@weyfringe.co.uk www.weyfringe.co.uk



Rewind Unit

The Multi-Compatible Label Rewind Unit

The Rewind Unit has a 180° idler arm allowing the rewind to be positioned with the open side most convenient for the operator. Loading is quick and simple and operation and running speeds are automatically matched to your printers output. The Rewind Unit can be used to unwind or rewind labels with a simple directional switch setting. Suitable for all table mounted label printers outputting labels to the below listed maximum size and speed.



Use 25mm, 38mm or 76mm cores



Coloured LED provides operation status



Rewind inside or outside wound label rolls



Stylish and rugged

Model	R-412	R-612
Paper width	120mm (4.72") Maximum	177.8mm (7") Maximum
Rewind speed	305mm/s (12 IPS)	
Label roll diameter	203.2mm (8") Maximum	
Core diameter	25mm (1") 38mm (1.5") 76mm (3")	
Label roll weight	3.48kg (7.6lbs)	5.22kg (11.5lbs)
Rewinding option	Labels inside OR labels outside	
Switches	Rewind control	
Motor	Hybrid motor	
Power	100 – 240 VAC 24W, 24V adaptor	
Environment	Operating temperature 5°C to 40°C (41°F to 104°F) Storage temperature -20°C to 60°C (-4°F to 122°F)	
Humidity	10% - 85% non-condensing	
Dimensions (H x W x D)	310mm (12") x 400mm (16") x 210mm (8")	
Agency approvals	CE, FCC Class A	
Weight	4.6kg (10.1lbs)	4.75kg (10.5lbs)
Warranty	12 months	