

T Series Barcode and Label Printer

Out-of-the-box Solution for Barcode Labels


Our top of the range T Series printers come with Easylabel Start software, interface cable, labels and a ribbon so you can just add a PC and start designing and printing labels right out of the box.

All this as well as 12 months warranty and free UK technical support for the life of the product.

T Series printers can print most types of labels so whether you need to identify pasties or pallets you can choose T Series with confidence.



View the current label on the colour touchscreen



Our Broadest range of standard interfaces



Touchscreen for quick and easy menu navigation



Weyfringe Labelling Systems

Longbeck Road | Marske-by-the-Sea | North Yorkshire | TS11 6HQ

Tel: 01642 490121 | Fax: 01642 490385

sales@weyfringe.co.uk www.weyfringe.co.uk



T Series Barcode and Label Printer

High Spec, fast and versatile

T Series printers adapt in line with your requirements by offering you the ability to swap between 203, 300 & 600 dpi print heads. USB, RS232 Serial and Ethernet interfaces are standard with optional Wi-Fi and Bluetooth available too. Add options such as external label rewinds, peel/dispenser packs, label cutters, wired and wireless mini keyboards (for no PC allowed environments) allowing you to tailor your T Series printer to match your requirements.



The high spec solution for printing barcode labels



Option for stand-alone no PC attached printing



Option for scan to print label



Create neat rolls of labels with optional external rewind

Model	T-4210	T-4307	T-4604
Resolution	203dpi (8 dot/mm)	300dpi (12 dot/mm)	600dpi (24 dots/mm)
Print Mode	Thermal Transfer / Direct Thermal		
Max. Print Speed	254mm/sec	177mm/sec	104mm/sec
Max. Print Length	4572mm	2159mm	660mm
Max. Print Width	108mm	105.7mm	105.6mm
Labels	Roll: Max. Diameter – 203mm Width: 25.4mm – 118mm		
Ribbon	Max. Length: 450m Width: 30mm – 110mm		
Software	EASYLABEL Start supplied FREE OF CHARGE		
Barcodes	Code 39, Code 93, Code 128 (subsets A,B,C), UCC/EAN-128, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions, I 2 of 5, EAN-8, EAN-13, Codabar, Postnet, DUN 14, Maxicode, Plessey, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Data Matrix & QR Code		
Interfaces	USB 2.0 – 3 x USB-A & 1 x USB-B RS232 Serial RJ45 Ethernet		
Real Time Clock	Standard		
Printer Dimensions	Length: 465mm Width: 305mm Height: 263mm Weight: 13.6Kg		
Options	Cutter Peel and Rewind Module Bluetooth Wi-Fi Module Parallel Port Adapter EASYLABEL Silver, Gold, Platinum and Multi-User		